

Product Data Sheet

Cellulose Tape, ESD Safe

758ST1653, 758ST045, 758ST044, 758ST162



- Charge decay of <0.014 seconds
- Used in binding, edging and securing

Product Information

Transparent ESD safe cellulose tape. Use in place of standard tape for packaging and around ESD sensitive products to seal static shielding bags, documents and to prevent damage to sensitive electronic components.

Technical Details

Typical Values

Total Thickness	2 mil
Adhesion to Steel	30 oz/in
Temperature	66°C
Tensile Strength	25 lb/in
Elongation	18%
Static Generation	< 250 volts @ 50% RH

Packaging

758ST1653	1/2" x 72 Yds, 3" core, 2 mil
758ST045	1" x 72 Yds, 3" core, 2 mil
758ST044	3/4" x 72 Yds, 3" core, 2 mil
758ST162	2" x 72 Yds, 3" core, 2 mil
10069922	1/4" x 72 Yds, 3" core, 2 mil

Compliance

RoHs/REACH Compliant: This Product complies with the European Union's "Restriction of Hazardous Substances" (RoHs) initiative and European REACH Regulation.

»» Techni-PRO

Wider selection | Higher quality | Stronger value

We've engineered a new private-label brand for world-class production supplies. You probably already know Techni-PRO products as Techni-Tool, Tec-Cut, Techni-Stat, Tec-Tuff, and other brands. Our goal was the same as it has always been: To give you more. More equipment. More supplies. More value.

Rev. JUN23